

PAT-NO: JP405311144A
DOCUMENT-IDENTIFIER: JP 05311144 A
TITLE: HEAT-RESISTANT
ADHESIVE
PUBN-DATE: November 22, 1993

INVENTOR-INFORMATION:

NAME	COUNTRY
INOUE, HIROSHI	
TAKABAYASHI, SEIICHIRO	
FUNAKOSHI, TSUTOMU	
SONOYAMA, KENJI	

ASSIGNEE-INFORMATION:

NAME	COUNTRY
UBE IND LTD	N/A

APPL-NO: JP04161599
APPL-DATE: May 12, 1992

INT-CL (IPC): C09J163/00 , C09J179/08 , C09J183/10

ABSTRACT:

PURPOSE: To provide the adhesive having a specific

composition, capable of laminating a heat-resistant film to a copper foil at a low temperature to give a laminate containing the adhesive layer having sufficient adhesiveness and excellent flexibility and heat-resistance and, accordingly, suitable for the production of a flexible printed circuit board, etc.

CONSTITUTION: The adhesive contains (A) 100 pts.wt. of a soluble polyimide siloxane produced by reacting an aromatic tetracarboxylic acid component composed mainly of a biphenyltetracarboxylic acid compound (preferably 2,3,3',4'-biphenyltetracarboxylic acid dianhydride) with 10-80mol% of a diaminopolysiloxane of formula (R is bivalent hydrocarbon group; R1 to R4 are lower alkyl or phenyl; n is 3-60) and 20-90mol% of an aromatic diamine (preferably 1,3-diaminodiphenyl ether, etc.), (B) 1-60 pts.wt. of an epoxy.polyoxyalkylene-modified polysiloxane, (C) 15-250 pts.wt. of other epoxy compound, (D) 0.2-20 pts.wt. of an inorganic filler and (E) an epoxy hardener as resin components.

COPYRIGHT: (C)1993,JPO&Japio